

Feature Group	IN112BB	IN114BB	IN114BBST
			
Image / Display			
Display System +2	DLP 0.55" DMD	DLP 0.55" DMD	DLP 0.55" DMD
Native Resolution +2	SVGA (800×600)	XGA (1024×768)	XGA (1024×768)
Native Aspect Ratio +2	4:3	4:3	4:3
Brightness (Bright/Eco) +2	3800 / 3040 Lumens	3800 / 3040 Lumens	3500 / 2800 Lumens
Contrast Ratio +2	30,000:1	30,000:1	30,000:1
Keystone Correction +2	±40 (Vertical)	±40 (Vertical)	±20 (Vertical)
Optical			
Lens Type +1	Manual Zoom & Focus	Manual Zoom & Focus	Fixed Lens, Manual Focus
Optical Zoom +1	1.1x	1.1x	Fixed 1:1
Throw Ratio +1	1.94:1 - 2.16:1	1.94:1 - 2.16:1	0.621:1
Focal Length (mm) +1	21.85 - 24.01	21.85 - 24.01	7.15
f number +1	2.41	2.41	2.7
Illumination			
Lamp Model +2	SP-LAMP-105	SP-LAMP-105	SP-LAMP-105
Lamp Life (Dynamic) +2	15,000 Hours	15,000 Hours	15,000 Hours
Lamp Power (Watts) +2	203	203	203
Connectivity			
Image Input +2	2x HDMI 1.4, VGA, S-Video	2x HDMI 1.4, VGA, S-Video	2x HDMI 1.4, VGA, S-Video
Image Output +2	1x VGA	1x VGA	1x VGA
Audio I/O +2	3.5mm In / 3.5mm Out	3.5mm In / 3.5mm Out	3.5mm In / 3.5mm Out
Control +2	RS232, IR Remote	RS232, IR Remote	RS232, IR Remote
Wireless Support +2	USB-A (5V/1.5A)	USB-A (5V/1.5A)	USB-A (5V/1.5A)
General			
Speaker +2	1x 10W (Mono)	1x 10W (Mono)	1x 10W (Mono)
Noise (Bright/Eco) +1	30 dB / 26 dB	30 dB / 26 dB	30 dB / 26 dB
Product Weight +1	2.6 Kg	2.6 Kg	2.6 Kg
24/7 Operation +1	Supported	Supported	Supported